

# Optional blackout plate for the Solatube® BrightenUp® Series

A retro-fit item suitable for the Solatube 160DS and 290DS Daylighting Systems (250 & 350mm diameter systems)

Simple, easy-to-use blackout coverplate stops daylight entering a room. Ideal for:  
Bedrooms | Cinema rooms | Classrooms | Office presentation rooms



## Parts list

	Qty
Metal ring sections	6
White diffuser cover plate with magnetic studs & twist fit mechanism	1
1200mm Twist lock pole	1

### To use the blackout coverplate with your Solatube Daylighting System:

1. Remove the diffuser from your Solatube Daylighting System by twisting it in an anti-clockwise direction.
2. Place the metal ring sections into the channel on the rear of the diffuser and replace the diffuser by twisting it clockwise into place.
3. Fix the pole to the diffuser cover plate by inserting it into the twist fit mechanism (twisting slightly anti-clockwise) and offer it up to the diffuser. The magnetic studs on the cover plate will locate with the metal ring sections and hold the diffuser in place.
4. Twist the pole clockwise to release it from the diffuser cover plate.
5. To remove the diffuser cover plate, insert the pole into the twist fit mechanism of the diffuser coverplate and pull down gently.



ML-INST-MBO-NL

SolaLighting Limited, 23 Osier Way, Olney Office Park, Olney MK46 5FP

Tel: 01234 241466 Fax: 01234 241766 Email: daylight@solatube.co.uk www.solatube.co.uk © Solalighting Limited